



Product Information: *ExCAL CW Calcium Carbonate
Medium Grades*

ExCAL CW Calcium Carbonate products are processed from a high purity ore, to exacting specifications at our Houston, Texas plant. These grades are processed for use in plastics, rubber, coatings, adhesives, sealants, mastics, and other specialty applications where color, binder demand and economics are of importance. These products are available in **50 lb. bags, 2,000 lb. bulk bags** and **bulk trucks**.

Typical Chemical Properties

Parameter	Wt., %
CaCO ₃	98.0
MgCO ₃	0.8
Fe ₂ O ₃	0.05
SiO ₂	<0.01
R ₂ O ₃	0.1
AL ₂ O ₃	0.95

Typical Physical Properties

	ExCAL CW 100	ExCAL CW 200	ExCAL CW 300	ExCAL CW 325
*Color	95	95	95	96
% Passing 200 Mesh	70	-	-	-
% Passing 325 Mesh	-	84	90	97
Median Particle Size	-	-	-	14
pH	7 - 8	7 - 8	7 - 8	7 - 8
Specific Gravity	2.7	2.7	2.7	2.7
% Moisture	0.1	0.1	0.1	0.1
Oil Absorption	-	-	13	14
% Acid Soluble	98	98	98	98
Bulk Density, lb/cu ft				
Loose	63	58	55	53
Packed	100	95	91	88

*Hunter Dry Brightness, L value

No warranty is expressed or implied regarding the accuracy of this data, the results to be obtained from the use thereof, or that any such will not infringe on any patent. Data on this sheet is furnished on the condition that the person receiving it shall make his own tests to determine the suitability thereof, for his particular purpose. In addition, since we cannot anticipate or control the many different conditions under which this information may be used, we do not guarantee the applicability or accuracy of this information or its suitability in any situation.